

## 465290240040

Miniature Industrial relay 8 - 16 A

## Downloaded from chalongroup.co.uk

	operating from 17.5 to 26.4 V, I	de/blade solder terminal, 2 pole, CO (nPDT), 8 A, AgNi, DC coil, 24 V rated power 0.5 W, resistance 1200 Ω, consumption 20 mA, holding oltage 2.4 V, option: Lockable test button + mechanical indicator, ) to +70 °C
This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.		BROWSE PRODUCT PAGE
Technical Features:		
Ambient temperature range:		-4070 Celsius Degrees
Commercial description:		Miniature industrial relay with 2 CO 8A contacts for socket mount or direct connection via Faston connectors. Equipped with AC or DC coil. Available with: lockable test button and mechanical and LED indicator. With Cadmium-free contacts. European patent.
Contact configuration:		2 pole, CO (nPDT)
Dimensions:		12.4x32.8x29 mm
Electrical life:		100000 cycles
Insulation coil/contacts:		6 KV 500
Nominal voltage dc:		24 Volts
Operating range dc:		17.526.4 Volts
Rated contact voltage:		250 V AC
Rated current (contacts):		8 Ampere
Rated power dc:		0.5 Watt
Supply:		DC coil
Certifications and quality ap	provals (according to type):	

The information, technical details, data and features contained in this document are subject to change or modification at any time. Downloaded in this document are subject to change or modification at any time. Downloaded in this document are subject to change or modification at any time. Downloaded in this document are subject to change or modification at any time. The basis of a contract.

> Need more information? Contact our sales Find a dealer