

465290120040

Miniature Industrial relay 8 - 16 A

Downloaded from chalongroup.co.uk



Technical description:

Miniature Industrial relay, Spade/blade solder terminal, 2 pole, CO (nPDT), 8 A, AgNi, DC coil, 12 V, operating from 8.8 to 13.2 V, rated power 0.5 W, resistance 300 Ω , consumption 40 mA, holding voltage 4.8 V, must drop-out voltage 1.2 V, option: Lockable test button + mechanical indicator, ambient temperature from -40 to +70 °C

This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

BROWSE PRODUCT PAGE

Technical Features:

Ambient temperature range:	-4070 Celsius Degrees
Commercial description:	Miniature industrial relay with 2 CO 8A contacts for socket mount or direct connection via Faston connectors. Equipped with AC or DC coil. Available with: lockable test button and mechanical and LED indicator. With Cadmium-free contacts. European patent.
Contact configuration:	2 pole, CO (nPDT)
Dimensions:	12.4x32.8x29 mm
Electrical life:	100000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage dc:	12 Volts
Operating range dc:	8.813.2 Volts
Rated contact voltage:	250 V AC
Rated current (contacts):	8 Ampere
Rated power dc:	0.5 Watt
Supply:	DC coil
Certifications and quality approvals (according to type):	

The information, technical details, data and features contained in this document are subject to change or modification at any time.

Dowlright information at any time.

Need more information?

Contact our sales Find a dealer