

**PDKA22BB10****Carton Box pieces****Qty** 1**Product**

Foot Switch

Model

with Hole for Metal Bar

Feature

Double

Contact

(1NO+1NC)+(1NO+1NC)

Color

Yellow

Protection

Metal Protection

Current**Ie** 3 A (240V AC)**Usage Category**

AC15

Mechanical Life**Min Qty** 1000000**Electrical Life****Min Qty** 100000**Operating Frequency****On-Off/Hour** Mech. 1800 Elec. 1200**Insulation Voltage****Ui** 300 V**Impulse Withstand Voltage****Uimp** 2.5 kV**Dielectric Strength (Body-Contact)**

2.500V AC

Dielectric Strength (Contact-Contact)

1.500V AC

Isolation Resistance

10 MΩ min. (500V DC)

Operating Temperature

-25 / +80 °C

Pollution Degree

3

Protection Degree

IP65

Contact Material

AgNi

Cable Section1.5-2.5 mm²**Screw Torque**

1.5Nm

Short Circuit Breaking Capacity**Ics** 1 kA**Body Material**

Plastic

Production Time

31.12.1899 00:00:00

Serial

PDK Series

Specifications

Plastic or Metal options

	Single and Double Speed
	Yellow
	Grey and orange color options
	with Latching option
Standards / Certificates	TS EN 60947-5-1 UL 508 VDE 0660
	
	

Chalong
solutions for control