

PVC Insulating Tape

General Purpose Insulating PVC Tape


Description:
Features:

- Material: PVC
- A high quality PVC Insulation Tape
- Manufactured to BS EN 60454-3 standards
- Flame retardant
- General purpose electrical tape
- Used for insulation, protection and fixing
- Harnessing of wires and cables
- Flexible with good protection against abrasion


Technical Data

Property	Value
Total Thickness	0.15mm (±0.02)
Elongation	125%
Tensile Strength	22 N/10 mm
Adhesion	Rubber based
- Steel	2.5 N/10 mm
- Self	2.5 N/10 mm
Temperature Rating	-18°C to +105°C
Flame Retardancy	Self extinguishing
Dielectric Strength	40 kV/mm

Item No.	Colour	W (mm)	L (m)	Thickness (mm)
PVC19x5-BLA	Black	19	5	0.15
PVC19x5-BLU	Blue	19	5	0.15
PVC19x5-BRN	Brown	19	5	0.15
PVC19x5-GRN	Green	19	5	0.15
PVC19x5-G/Y	Green Yellow	19	5	0.15
PVC19x5-GRY	Grey	19	5	0.15
PVC19x5-RED	Red	19	5	0.15
PVC19x5-WHT	White	19	5	0.15
PVC19x5-YLW	Yellow	19	5	0.15

Product technical table
continues on next page

PVC Insulating Tape

General Purpose Insulating PVC Tape

PVC19x20-BLA	Black	19	20	0.15
PVC19x20-BLU	Blue	19	20	0.15
PVC19x20-BRN	Brown	19	20	0.15
PVC19x20-G/Y	Green Yellow	19	20	0.15
PVC19x20-GRN	Green	19	20	0.15
PVC19x20-GRY	Grey	19	20	0.15
PVC19x20-RED	Red	19	20	0.15
PVC19x20-WHT	White	19	20	0.15
PVC19x20-YLW	Yellow	19	20	0.15
PVC19x20-ORANGE	Orange	19	20	0.15
PVC19x20-PURPLE	Purple	19	20	0.15
PVC19x33-BLA	Black	19	33	0.15
PVC19x33-BLU	Blue	19	33	0.15
PVC19x33-BRN	Brown	19	33	0.15
PVC19x33-G/Y	Green Yellow	19	33	0.15
PVC19x33-GRN	Green	19	33	0.15
PVC19x33-GRY	Grey	19	33	0.15
PVC19x33-RED	Red	19	33	0.15
PVC19x33-WHT	White	19	33	0.15
PVC19x33-YLW	Yellow	19	33	0.15
PVC19x33-ORANGE	Orange	19	33	0.15
PVC19x33-PURPLE	Purple	19	33	0.15
PVC50x33-BLA	Black	50	33	0.15
PVC50x33-BLU	Blue	50	33	0.15
PVC50x33-BRN	Brown	50	33	0.15
PVC50x33-G/Y	Green Yellow	50	33	0.15
PVC50x33-GRN	Green	50	33	0.15
PVC50x33-GRY	Grey	50	33	0.15
PVC50x33-RED	Red	50	33	0.15
PVC50x33-WHT	White	50	33	0.15
PVC50x33-YLW	Yellow	50	33	0.15

The above information is given only as a guide, the user should ensure that the performance of the product is sufficient for application.

The quoted values are average and should not be taken as maximum or minimum values for specific purposes.

KrimpTerm cannot be held responsible for product failure unless full testing has been carried out.

The user has to decide on the tapes suitability for their own applications.