

Quick Disconnects

Bullet Female Quick Disconnects

• Materials:

Conductor: Brass
Sleeve: Copper tubular
Insulation: Vinyl
Plating: Tin

• Operating Temperature:



-10°C to +75°C.

• Features:

Max. voltage rating: 300V.
Flared barrel for easy wire insertion.
Low insertion force and easy crimping whilst ensuring secure termination.


Material

- ① Brass
- ② Tin
- ③ Vinyl
- ④ Copper

Standard Internal Copper Sleeve

Long Internal Copper Sleeve

Max. current rating

Red	10A
Blue	15A
Yellow	24A

See product technical table
on next page

Quick Disconnects

Bullet Female Quick Disconnects

Item No.	Colour	Wire Range (mm ²)	Dimensions (mm)					
			B	C	D	W	L	F
RBR40	Red	0.5-1.5	10.5	1.7	3.8	3.9	25.5	7.3
RBR40L	Red	0.5-1.5	10.5	1.7	3.8	3.9	25.5	7.3
BBR40	Blue	1.5-2.5	10.5	2.3	4.7	3.9	25.5	7.3
BBR50	Blue	1.5-2.5	10.5	2.3	4.7	4.9	25.5	8.5
BBR50L	Blue	1.5-2.5	10.5	2.3	4.7	4.9	25.5	8.5
YBR50	Yellow	4.0-6.0	13.7	3.4	6.2	4.9	28.0	8.5
YBR50L	Yellow	4.0-6.0	13.7	3.4	6.2	4.9	28.0	8.5

L suffix on Item No. denotes long internal copper sleeve.