

553490120094

General purpose relay 7 - 10 A

Downloaded from chalongroup.co.uk



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:

Industrial relay, Plug-in socket version, 4 pole, 7 A, DC coil, 12 V, operating from 9.6 to 13.2 V, rated power 1 W, resistance 140 Ω, consumption 86 mA, holding voltage 6 V, must drop-out voltage 1.2 V, Contact material: AgNi, CO (SPDT), Options: Lockable test button + LED + diode (DC, polarity positive to pin A1/13), ambient temperature from -40 to +85 °C

BROWSE PRODUCT PAGE

Technical Features:

Ambient temperature range:	-40...85 Celsius Degrees
Commercial description:	General purpose plug-in relay. 4 CO 7 A. For use with 94 Series sockets. AC or DC coil. Lockable test button option and mechanical indicator as standard Variant with LED and integrated protection circuit.
Contact configuration:	4 pole, CO (nPDT)
Dimensions:	20.7x37.2x27.7 mm
Electrical life:	150000 cycles
Insulation coil/contacts:	4 kV
Nominal voltage dc:	12 Volts
Operating range dc:	9.6...13.2 Volts
Rated contact voltage:	250 V AC
Rated current (contacts):	7 Ampere
Rated power dc:	1 Watt
Supply:	DC coil

Certifications and quality approvals (according to type):



The information, technical details, data and features contained in this document are subject to change or modification at any time.  
It is for information purposes only and does not form the basis of a contract.

Downloaded from chalongroup.co.uk

Need more information?

[Contact our sales](#) [Find a dealer](#)