

553482300054

General purpose relay 7 - 10 A

Downloaded from chalongroup.co.uk



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:

Industrial relay, Plug-in socket version, 4 pole, 7 A, AC coil, 230 V, operating from 184 to 253 V, rated power 1.5 VA, resistance 17000 Ω, consumption 6 mA, holding voltage 184 V, must drop-out voltage 46 V, Contact material: AgNi, CO (SPDT), Options: Lockable test button + LED (AC) + mechanical indicator, ambient temperature from -40 to +85 °C

BROWSE PRODUCT PAGE

Technical Features:

Ambient temperature range:	-40...85 Celsius Degrees
Commercial description:	General purpose plug-in relay. 4 CO 7 A. For use with 94 Series sockets. AC or DC coil. Lockable test button option and mechanical indicator as standard Variant with LED and integrated protection circuit.
Contact configuration:	4 pole, CO (SPDT)
Dimensions:	20.7x37.2x27.7 mm
Electrical life:	150000 cycles
Insulation coil/contacts:	4 kV
Nominal voltage ac:	230 Volts
Operating range ac:	184...253 Volts
Rated contact voltage:	250 V AC
Rated current (contacts):	7 Ampere
Rated power ac:	1.5 VA
Supply:	AC coil

Certifications and quality approvals (according to type):



The information, technical details, data and features contained in this document are subject to change or modification at any time.  
It is for information purposes only and does not form  
part of a contract.  
Downloaded from chalongroup.co.uk

Need more information?

Contact our sales Find a dealer