

465280240040

Miniature Industrial relay 8 - 16 A

Downloaded from chalongroup.co.uk



Technical description:

Miniature Industrial relay, Spade/blade solder terminal, 2 pole, CO (nPDT), 8 A, AgNi, AC coil, 24 V, operating from 19.2 to 26.4 V, rated power 1.2 VA, resistance 320 Ω , consumption 45 mA, holding voltage 19.2 V, must drop-out voltage 4.8 V, option: Lockable test button + mechanical indicator, ambient temperature from -40 to +70 °C

This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

BROWSE PRODUCT PAGE

Technical Features:

| Ambient temperature range: | -4070 Celsius Degrees |
|-----------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Commercial description: | Miniature industrial relay with 2 CO 8A contacts for socket mount or direct connection via Faston connectors. Equipped with AC or DC coil. Available with: lockable test button and mechanical and LED indicator. With Cadmium-free contacts. European patent. |
| Contact configuration: | 2 pole, CO (nPDT) |
| Dimensions: | 12.4x32.8x29 mm |
| Electrical life: | 100000 cycles |
| Insulation coil/contacts: | 6 kV |
| Nominal voltage ac: | 24 Volts |
| Operating range ac: | 19.226.4 Volts |
| Rated contact voltage: | 250 V AC |
| Rated current (contacts): | 8 Ampere |
| Rated power ac: | 1.2 VA |
| Supply: | AC coil |
| Certifications and quality approvals (according to type): | |

The information, technical details, data and features contained in this document are subject to change or modification at any time.

Downition at any time.

Downition at any time.

Need more information?

Contact our sales Find a dealer