

## 465282300040

## Miniature Industrial relay 8 - 16 A

## Downloaded from chalongroup.co.uk

	operating from 184 to 253 V, ra	de/blade solder terminal, 2 pole, CO (nPDT), 8 A, AgNi, AC coil, 230 V ated power 1.2 VA, resistance 28000 Ω, consumption 5 mA, holding voltage 46 V, option: Lockable test button + mechanical indicator, ) to +70 °C
This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.		BROWSE PRODUCT PAGE
Technical Features:		
Ambient temperature range:		-4070 Celsius Degrees
Commercial description:		Miniature industrial relay with 2 CO 8A contacts for socket mount or direct connection via Faston connectors. Equipped with AC or DC coil. Available with: lockable test button and mechanical and LED indicator. With Cadmium-free contacts. European patent.
Contact configuration:		2 pole, CO (nPDT)
Dimensions:		12.4x32.8x29 mm
Electrical life:		100000 cycles
Insulation coil/contacts:		6 KV
Nominal voltage ac:		230 Volts
Operating range ac:		184253 Volts
Rated contact voltage:		250 V AC
Rated current (contacts):		8 Ampere
Rated power ac:		1.2 VA
Supply:		AC coil
Certifications and quality ap	provals (according to type):	

The information, technical details, data and features contained in this document are subject to change or modification at any time. Downloaded in this document are subject to change or modification at any time. Downloaded in this document are subject to change or modification at any time. Downloaded in this document are subject to change or modification at any time. The basis of a contract.

> Need more information? Contact our sales Find a dealer